

UKL AIR ELIMINATOR TRAP :-

•UKL Air Eliminator trap removes the trapped air from liquid lines/process equipments. Air is a harmful ingredient in steam going to process areas. Presence of air aids corrosion and leakage from pipelines and from vessels. Air can enter steam space through Boiler Feed Water circuit. Air can enter from atmosphere when steam condenses over long stoppages.

During start up when the air from liquid lines/process equipment enters Air eliminator trap, it passes through outlet port, when the liquid enters the Air Eliminator Trap the float rises and closes the outlet port and restrict the liquid to flow out.



MATERIAL OF CONSTRUCTION:

CAST IRON MODEL

UAET-14 Model– IS 210 FG260

CAST CARBON STEEL MODEL

UAET- 20 Model- ASTM A216 Gr. WCB

OPERATING CONDITIONS:-

UAET-14 CAST IRON MODEL

Max Operating Pressure :- 13.26 Kg/cm²

Max Operating Temperature :- 220 °C

UAET-20 CAST CARBON STEEL MODEL

Max Operating Pressure :- 32 Kg/cm²

Max Operating Temperature :- 425 °C

| Model | Max Diff. Pressure | PMO (Kg/cm ²) | Sat. Temp °C |
|--------------|------------------------|---------------------------|--------------|
| UAET-14 -4.5 | 4.5 Kg/cm ² | 14 | 193 |
| UAET-14 -10 | 10 Kg/cm ² | 14 | 193 |
| UAET-14 -14 | 14 Kg/cm ² | 14 | 193 |
| UAET-20 -4.5 | 4.5 Kg/cm ² | 32 | 237 |
| UAET-20-10 | 10 Kg/cm ² | 32 | 237 |
| UAET-20-14 | 14 Kg/cm ² | 32 | 237 |
| UAET-20-21 | 21 Kg/cm ² | 32 | 237 |
| UAET-20-32 | 32 Kg/cm ² | 32 | 237 |

SIZES AVAILABLE:-

UAET-14 Model: 15 NB, 20 NB and 25 NB

UAET-20 Model: 15 NB, 20 NB and 25 NB

OPTIONAL:-

IBR/Non-IBR

Inbuilt Strainer

Flanged End #150/#30

Available Diff. Pressure (Kg/cm²)

UAET-14 Model :- 4.5/10/14

UAET-20 Model :-4.5/10/14/21/32

END CONNECTIONS:

UAET-14 CAST IRON MODEL

Threaded to NPT , BSP and BSPT.

UAET-20 CAST CARBON STEEL MODEL :-

Threaded to NPT , BSP and BSPT.

Socket Weld to ASME B 16.11

Flanged End #150/#300 (On Request)


INSTALLATION :-

Horizontal/Vertical position.

BILL OF MATERIAL:

UAET14/UAET-20

Size- 15 NB/20 NB/25 NB



| No. | PART NAME | MATERIAL | MATERIAL CODE | MATERIAL | MATERIAL CODE |
|-----|-------------------|--------------|-------------------|--------------|---------------|
| 1 | Body | Cast Steel | ASTM A 216 Gr WCB | Cast Iron | IS 210 FG 260 |
| 2 | Cover | Cast Steel | ASTM A 216 Gr WCB | Cast Iron | IS 210 FG 260 |
| 3 | Pivot Pin | SS | AISI 304 | SS | AISI 304 |
| 4 | Valve Seat | SS | AISI 304 | SS | AISI 304 |
| 5 | Pivot Bracket | SS | AISI 304 | SS | AISI 304 |
| 6 | Float Halves | SS | AISI 304 | SS | AISI 304 |
| 7 | Lever | SS | AISI 304 | SS | AISI 304 |
| 8 | Steel Ball | SS | SS 440C | SS | SS 440 C |
| 9 | Cover Gasket | CAF | CAF | CAF | CAF |
| 10 | Valve Seat Gasket | SS | AISI 304 | SS | AISI 304 |
| 11 | Cover Bolt (M10) | Carbon Steel | Gr. 8.8 | Carbon Steel | Gr. 8.8 |
| 12 | Name Plate | SS | AISI 304 | SS | AISI 304 |
| 13 | Strainer | SS | AISI 304 | SS | AISI 304 |

Screwed / Socket Weld End Connections

| Size | Diff Pressure | A | B | C | D | E | F | Weight (kg) |
|-------|---------------------------------|-----|-----|----|-----|----|-----|-------------|
| 15 NB | 4.5/10/14 Kg/cm ² | 128 | 111 | 68 | 179 | 30 | 110 | 3.500 |
| 20 NB | | 128 | 111 | 68 | 179 | 30 | 110 | 3.500 |
| 25 NB | | 153 | 111 | 75 | 202 | 30 | 130 | 5.000 |



Cast / Forged Steel Piston Valves, Bellow seal valves, High Pressure valves (Gate/Globe), Strainers – “Y” Type, ITVS Steam Traps (Thermodynamic, Thermostatic, Ball Float Traps and IBT), Pressure Reducing Station, Condensate Recovery Products. Level Gauges (Reflex, Transparent, Bicolor), Sight Glass, Hot Water Generation System, Safety and Relief Valves. FSD Products : Compressed Asbestos / Non Asbestos Fiber Sheeting / Cut Gaskets, Spiral Wound Gaskets.

In view of technical progress design and dimensions are subjected to change without notice.



UNI KLINGER LIMITED

A joint venture of the Neterwala group of companies and KLINGER AG. Switzerland.

Central Sales Office & Pune Branch : SC1, 5th Fl., Kohinoor Est. Mumbai-Pune Highway, Kadaki, Pune-411 003. Tel.: +91-20-4102 3000 Fax.: (020) 4102 3001 e-mail : salesco@uniklinger.com, salespune@uniklinger.com, Website : www.uniklinger.com

Factory : C-37, M.I.D.C., Ahmednagar – 414 111, Maharashtra, Tel. : 0241 – 2777223 / 2777512 Fax : 0241 – 2777294, E-mail : fdworks@uniklinger.com

Branch Offices :

Baroda : 102, 1st Floor, Otel Towers-II R.C. Dutt Road, Baroda-390 005, Tel.: 91-0265-2312343 / 2340660, Fax.: 91-265-2341419. E-mail : salesbar@uniklinger.com
Chennai : East Coast Centre, 5th Floor, 553, Mount road, Teyanampet, Chennai - 600 018, Tel.: 91 - 44 - 24345707. Fax.: 91 - 44 - 24343960. E-mail : saleschen@uniklinger.com
Kolkata : 9, Chittrakoot, 8th Floor, 230 A, AJC Bose road, Kolkatta-700 020, Tel.: 91-33-22872510, Fax.: 91-33-22876494. E-mail : salescal@uniklinger.com
Mumbai : 22, 2nd Flr, Shreeji Arcade CHS, Almeda road, Thane-400 602, Tel.: 91-22-25421140 / 91-22-25440461, Fax.: 91-22-25440463. E-mail : salesmum@uniklinger.com
Delhi : 321, Ansal Chamber-II, 6, Bhikaji Cama Place, New Delhi-110 066, Tel.: 91-11-41658767 / 91-11-26193847, Fax.: 91-11-41658768. E-mail : salesdel@uniklinger.com